



**NANO
EVERO**
Advanced Nanocoating



APPLICATION MANUAL

Vetro Power NANO-EVERO Universal Protection

Corrosion & Moisture Protection with Dewatering Action

PRODUCT SPECIFICATION

VETRO POWER NANO-EVERO UNIVERSAL PROTECTION is a corrosion and dewatering protection. Due to its ability to form a flexible, greasy film on the surface of the coated objects, it can be used to protect PCB's and other electronic devices from getting short circuited by water or humidity, moisture, dampness, condensation and flooding and also protects the parts from corrosion. Vetro Power NANO-EVERO Universal Protection can be applied at room temperature by spraying, dipping or painting.

MATERIAL INFORMATION

Basis	Preparation of corrosion protection
Look	Transparent, brownish liquid
pH-Value	n.d
Active Agent	n.d
Viscosity (DIN 53211)	n.d. sec
Thinning	Ready to use formula
Application	10-50 ml/m ² (Depending on surface /application/thickness of layer)
Handling	See MSDS
Working Conditions	-40°C - +40°C

Shelf Life	Min. 12 Months
Storage temp.	+5°C - +25°C (Store dark and frost resistant)

APPLICATION

Wear gloves and a mask using **VETRO POWER NANO-EVERO UNIVERSAL PROTECTION**. Keep away from open fire and make sure for good ventilation. Apply in three Steps: 1. Cleaning 2. Application 3. Drying

1. Cleaning :

Make sure the surface is free of fat, dust, water, etc. (use alcohol, basic or acid cleaners). Material has to be dry.

2. Application :

Vetro Power NANO-EVERO Universal Protection has to be applied by spraying, dipping or painting on the surface of the to be coated device. Make sure that the product can reach every area that shall be protected. Please let the material drip off for a few minutes.

3. Drying :

The coating will not dry out/harden. There will remain an oily residue on the treated objects.

Warning Advice: We recommend wearing suitable protective clothing. In case of contact with skin, immediately rinse off with water. Do not swallow. Avoid contact with eyes. In case of contact with the eye or mucosa, immediately rinse off with water. In the event of symptoms occurring, seek medical treatment. Keep out of reach of children!

General advice: Do not inhale atomised spray and the liquid product.

Zyax Chem PVT LTD is not liable for damages to the product, as a result of dirt entering the bottles and canisters, e.g. after opening the containers. Zyax Chem PVT LTD is also not liable for improper application of the product if the surfaces have been recoated for any reasons, without Zyax Chem PVT LTD's prior written agreement, nor for any damage to or deterioration of the coating system arising from causes beyond the control of Zyax Chem PVT LTD, including but not limited to impact, abrasion, mechanical damage, neglect, malicious damage, fire damage, pollution and abnormal weather conditions, neither for failure associated with exposure of the coatings to abrasive, chemical substances, abrasive scouring, hydrofluoric acid and highly alkaline chemicals such as bleach, potassium hydroxide and sodium hydroxide and/or if the coated surfaces have not been maintained in accordance with the supplier's recommended maintenance procedures. All information is based on today's state-of-the-art technology. As to the above-mentioned information, we do not lay a claim to completeness, these are only to be understood as possible examples for application areas. Due to a large number of surfaces and object conditions, the buyer/user is not relieved of the duty to professionally verify, in his own responsibility, that our materials are suitable for the intended purpose according to the respective object conditions. In all other respects, our general conditions of sale apply. If the new product information is issued the validity of the old version expires.

VETRO POWER INDIA

ZYAX CHEM PVT LTD

Third Floor, Kamer Building, 38, Cawasji Patel Street, Fort, Mumbai, Maharashtra, 400001, India.

☎ +91-887-900-9911 | ✉ customercare@vetropower.com | 🌐 www.vetropoweramc.com