

# Vetro Power Nano-Dynamis Anti-Corrosion Protection

## MATERIAL SAFETY DATA SHEET (MSDS)

### SECTION 1: Identification of the substance/ mixture and of the company/ undertaking

#### 1.1. Product identifier

Product name : Vetro Power Nano-Dynamis Anti-Corrosion Protection  
Product code : -

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. For coating of non-porous surfaces to provide protection against corrosion

#### 1.3. Details of the supplier of the safety data sheet

**ZYAX CHEM PVT. LTD.,**  
3rd Floor, Kamer Building,  
38 Cawasji Patel Street, Fort,  
Mumbai - 400001, India.  
Contact No: +91 8779240420  
info@zyax.in - www.zyax.in

#### 1.4. Emergency telephone number

Emergency number : +91 22 2757 3899

### SECTION 2: Hazards identification

Hazard statement :

H226 Flammable liquid and vapour  
H302 +H312 +H332 Harmful if swallowed, in contact with skin or if inhaled  
H314 Causes severe skin burns and eye damage.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness  
H412 Harmful to aquatic life with long lasting effects

Precautionary Statement (Prevention) :

P210 Keep away from heat/sparks/open flames/hot surfaces – no smoking  
P233 Keep container tightly closed  
P240 Ground/bond container and receiving equipment  
P241 Use explosion-proof electrical/ventilating/lighting/...../equipment  
P242 Use only non-sparking tools  
P243 Take precautionary measures against static discharge  
P260 Do not breathe dust/fume/gas/mist/vapours/spray.  
P261 Avoid breathing dust/fume/gas/mist/ vapours/spray  
P264 Wash skin thoroughly after handling  
P270 Do not eat, drink or smoke when using this product  
P271 Use only outdoors or in a well-ventilated area  
P280 Wear protective gloves/protective clothing/eye protection/face protection

## Vetro Power Nano-Dynamis Anti-Corrosion Protection

## Safety Data Sheet

### Precautionary Statement (Response) :

P301 + P312 + P330 IF SWALLOWED:

Call a POISON CENTER or doctor/ physician if you feel unwell. Rinse mouth. Do NOT induce vomiting.

P302 + P352 + P312 IF ON SKIN:

Wash with plenty of water. Call a POISON CENTER or doctor/ physician if you feel unwell.

P303+P361+P353 If on skin or hair:

remove/take off immediately all contaminated clothing.

Rinse skin with water/shower

P304 + P340 +P310 P312 F INHALED:

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/ physician

P305 + P351 + P338 + P310 IF IN EYES:

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.

P312

Call a POISON CENTER or doctor/physician if victim feels unwell

P370+P378 In case of fire:

Use dry sand, dry chemical or alcohol-resistant foam for extinction.

P332 + P313 If skin irritation occurs:

Get medical advice/ attention.

P337 + P313 If eye irritation persists:

Get medical advice/ attention.

P333 + P313 If skin irritation or rash occurs:

Get medical advice/ attention.

P363

Wash contaminated clothing before reuse.

### Precautionary Statement (Storage) :

P403+P233+P235

Store in a well-ventilated place. Keep cool. Keep container tightly closed.

P405

Store locked up.

### Precautionary Statement (Disposal) :

P501

Dispose of contents/container to an approved waste disposal plant.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### Chemical Characterisation Ingredients

Ingredient	CAS Number	EC Number	Content
Organic polysilane compoundI			>30% <50%
3-Aminopropyltriethoxysilane	919-30-2	213-048-4	> 5% <10%
Toluene	108-88-3	203-625-9	>1%
n-butanol acetate	123-86-4	204-658-1	>50% <70%

## SECTION 4: FIRST AID MEASURES

### General Advice:

Remove contaminated or saturated clothing

### Inhalation:

Remove victim from exposure. Take affected persons out into the fresh air. In case of persistent discomfort seek medical attention

### Ingestion:

Have the mouth rinsed with water. Have the patient drink plenty of water in small sips. Do not induce vomiting. Obtain medical attention.

### Skin Contact:

Wash off immediately with plenty of water. If swelling, redness, blistering or irritation occurs seek medical advice.



## Vetro Power Nano-Dynamis Anti-Corrosion Protection

## Safety Data Sheet

Eye contact:	Keeping eyelid open, immediately rinse thoroughly for at least 5 minutes using plenty of water or, eye rinsing solution. Seek medical attention
Notes to physician:	If required, therapy of irritative effect. After absorbing large amounts of substance: administration of activated charcoal. Acceleration of gastrointestinal passage

### SECTION 5: Firefighting measures

Specific Measures:	Caution: Use of water spray when fighting fire may be insufficient. Small fire: use foam, dry chemical, CO2 or water spray. Large Fire: Use foam, fog or water spray – Do not use water jets.
Specific Hazards:	HIGHLY FLAMMABLE If safe to do so move undamaged containers from fire area. Cool containers with water until well after fire is out. Avoid getting water inside containers. 3Y
Hazchem Code: Precautions for Firefighters:	Wear respiratory protection equipment. Fully-encapsulated, gas tight suits should be worn for maximum protection

### SECTION 6: Accidental release measures

Personal precautions:	Protective clothing should be worn to prevent excessive skin contact.
Environmental Precautions:	Prevent liquid entering sewers. Do not allow to enter surface waters, storm drains, etc.
Small spills:	Take immediate steps to stop and contain the spill. Caution should be excised regarding personnel safety and exposure to be spilled material. Eliminate all sources of ignition and wear protective clothing. Absorb small spills onto paper towels and evaporate in a safe place. Flush the contaminated area with plenty of water. Stop leak if you can do it without risk. Eliminate all sources of ignition and static; restrict access to area until completion of clean-up procedure. Wear adequate protective equipment, use self-contained breathing apparatus in confined poorly-ventilated areas.
Large spills:	Large quantities should be absorbed on to sand, earth or non combustible absorbent material and removed to a safe area for disposal. Flush the contaminated area with plenty of water.

### SECTION 7: HANDLING AND STORAGE

Handling and Storage:	Avoid contact with skin or in eyes. Do not inhale vapour or mist. Keep away from sources of ignition - No smoking. Take measures to prevent the build-up of electrostatic charge. Open and handle container with care. Keep away from open fire. Keep away from heating sources. Keep away from sources of ignition
Conditions for safe Storage:	Keep container tightly closed in a cool, dry and well-ventilated place away from direct sunlight and other sources of heat or ignition. Store away from oxidising agents. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Check regularly for leakage. Open container in order to release pressure which may be generated (ammonia).
Storage Regulations:	Refer Australian Standard AS 1940 -2004 "the storage and handling of flammable and combustible liquids".
Storage class:	3 flammable liquid

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

**National Exposure Standard:**

Name	CAS No	STEL (mg/m <sup>3</sup> )	STEL (ppm)	TWA (mg/m <sup>3</sup> )	TWA (ppm)
Toluene	108-88-3	574	150	191	50
3-Aminopropyltriethoxysilane	919-30-2	{Contains no substances with occupational exposure limit values.}			
n-Butanol					
Acetate	123-86-4	713	150	950	200
Organic Polysilane Compound	n/a				

**Other Exposure Information**

The exposure value at the TWA is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL is the maximum average concentration to which an unprotected worker may be exposed in any fifteen-minute interval during the day. Any fifteen-minute periods in which the average STEL concentration exceeds the permissible level must be separated from each other by at least one hour.

**Appropriate Engineering Controls :**

In industrial situations maintain the concentrations values below the TWA. This may be achieved by process modification, use of local exhaust ventilation, capturing substances at the source, or other methods.

**Respiratory Protection:**

Where ventilation is not adequate, respiratory protection may be required. Avoid breathing vapours or mists. Select and use respirators in accordance with AS 1716 – Respiratory Protective Devices and be selected in accordance with AS 1715 – Selection, Use and Maintenance of Respiratory Protective Devices.

**Eye Protection:**

The use of a face shield, chemical goggles or safety glasses with side shield protection as appropriate. Must comply with Australian Standards AS 1337 and be selected and used in accordance with AS 1336.

**Skin Protection:**

Hand protection should comply with AS 2161, Occupational protective gloves – Selection Use and Maintenance. Recommendation: PVC, neoprene or nitrile rubber gloves.

**Other Protective Clothing Equipment:**

Impermeable clothing. Final choice of personal protective equipment will depend on individual circumstances and/or according to risk assessments undertaken..

Always wash hand before smoking, eating or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

**Hygienic Measures:**

Safety boots in industrial situations is advisory. Foot protection should comply with AS 2210, occupational protective footwear- Guide to selection, care and use.

**Footwear:**

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

Form:	Liquid
Appearance:	Colourless
Odor:	slightly ammonia-like
Melting Point:	N/A
Boiling Point:	not available
Solubility in Water:	Reacts with water
Flash Point: :	16 °C
Vapor Pressure:	not available
Specific Gravity:	not available
Relative Density:	0.92 g/m3 (at 20o C)
Ignition Temp.	ca. 435 °C
Evaporation Rate:	not available
Explosion Limits:	lower: not available upper: not available
pH (500 g/l H2O):	not available
Dynamic viscosity:	not available
Kinematic viscosity	not available
Volatile Organic Compounds (VOC):	not available

**SECTION 10: STABILITY AND REACTIVITY**

Chemical Stability:	The material can slowly hydrolyze in the presence of water to form hydrogen and ammonia gases and condensed siloxane., pressure build-up
Conditions to Avoid	Heat, sparks, flame, direct sunlight and build up of static electricity.
Incompatibility (Material To Avoid):	oxidizing agents, bases, acids,halogenated compounds. Reacts with moisture, water, alchhols and amines to produce ammonia.
Hazardous Decomposition	Decomposition products Hydrogen and Ammonia

**SECTION 11: TOXICOLOGICAL INFORMATION**

Toxicolglal Effects:	Acute toxicity  LD50 Oral (Rat) 636 mg/kg (tulene) LD50 Dermal (Rabbit) 12,124 mg/kg (tulene) LC50 Inhalation (Rat) 4 h > 12,500 – 28,800 mg/m3 (tulene)  LD50 Oral (Rat) 1,780 mg/kg (3-Aminopropyl triethoxysilane) LD50 Dermal (Rabbit) 3,800 mg/kg (3-Aminopropyl triethoxysilane) LC50 Inhalation (Rat) Not available  LD50 Oral (Rat) 13100 mg/kg (n-Butanol Acetate) LD50 Dermal (Rabbit) >5000 mg/kg (n-Butanol Acetate) LC50 Inhalation (Rat) 4 h > 21.0 mg/l (n-Butanol Acetate)
Other Information:	Chronic effects on Humans – nota available Toxic effects on Humans – not available

## Vetro Power Nano-Dynamis Anti-Corrosion Protection

## Safety Data Sheet

General:	From our experience and the information provided to us this product does present any adverse health effects if the product is handled in accordance with this Material Safety Data Sheet and product label.
Ingestion:	May cause nausea, vomiting, headache, dizziness and gastric irritation
Eye Contact:	May cause irritation and watering. High concentration of vapours may cause irritation.
Skin Contact:	Contact with the skin may result in irritation
Inhalation:	Where the material is used in a poorly ventilated area, at elevated temperature or in confined spaces, vapour may cause irritation to the mucous membranes of the respiratory tract. May cause headaches, dizziness and nausea.

### SECTION 12: ECOLOGICAL INFORMATION

Ecological Information:	No ecological problems are expected to occur when the product is handled and used with due care and attention
Ecotoxicity:	Avoid contaminating waterways
Further Information:	no ecotoxicological study available

### SECTION 13: DISPOSAL CONSIDERATIONS

Disposal Considerations :	Whatever cannot be saved for recovery or recycling should be disposed of according to relevant local authority, state and federal government regulations.
---------------------------	---

### SECTION 14: TRANSPORT INFORMATION

	<b>Land Transport ADR/RID/GGVS/GGVE</b>	<b>Sea Transport (IMDG / IMO)</b>	<b>Air Transport (IATA / ICAO)</b>
UN Number	2924	2924	2924
Proper Shipping Name	3-Aminopropyltriethoxsilane, Butanols	3-Aminopropyltriethoxsilane, Butanols	3-Aminopropyltriethoxsilane, Butanols
DG Class	3	3	3
Hazchem Code	3YE	3YE	3YE
Packaging Group	II	III	II
Marine pollutant	no	no	no

### SECTION 15: REGULATORY INFORMATION

Classification:	Highly Flammable
Poisons Schedule:	Not scheduled



### SECTION 16: OTHER INFORMATION

#### DISCLAIMER:

The information contained in this Material Safety Data Sheet (MSDS) is believed to be correct and was obtained from sources we believe are reliable. However, since data, safety standards and government regulations are subject to change and the conditions of handling and use, or misuse are beyond our control, we make no warranty either expressed or implied, with respect to the completeness or accuracy to the information contained herein. Trifli Technologies Pvt. Ltd. (India) makes no representations, guarantees or warranties of any kind as to the accuracy, suitability for particular applications, hazards connected with the use of the material, or the results to be obtained from the use thereof. User assumes all risks and liability of any use, processing or handling of any material, variations in methods, conditions and equipment used to store, handle or process the material and hazards connected with the use of the material are solely the responsibility of the user and remain at their sole discretion. Compliance with all applicable federal, state, and local laws and regulations remains the responsibility of the user, and the user has the responsibility to provide a safe work place, to examine all aspects of its operation and to determine if or where precautions, in addition to those described herein, are required.